


Super Fast Recovery Diode

RFU20TM5S



•Absolute maximum ratings(Tc=25°C)


Parameter	Symbol	Conditions	Limits	Unit
Repetitive peak reverse voltage	V _{RM}	Duty⊴0.5	530	V
Reverse voltage	V _R	Direct voltage	530	V
Average rectified forward current	lo	60Hz half sin wave, Resistance load, Tc=95°C	20	A
Forward current surge peak	I _{FSM}	60Hz half sin wave, Non-repetitive one cycle peak value, Tj=25°C	100	A
Junction temperature	Tj	ELECT	150	°C
Storage temperature	Tstg		-55to+150	°C

•Electrical characteristics(Tj=25°C)


Parameter	Symbol	Conditions	Min.	Тур.	Max.	Unit
Forward voltage	V _F	I _F =20A	-	1.65	2	V
Reverse current	I _R	V _R =530V	-	0.05	10	μA
Reverse recovery time	trr	I _F =0.5A,I _R =1A,Irr=0.25×I _R	-	23	30	ns
Thermal Resistance	Rth(j-c)	junction to case	-	-	1.8	°C/W

©2009 ROHM Co., Ltd. All rights reserved. Published by WWW.SKYT22001H.Rey.A


Electrical characteristic curves



©2009 ROHM Co., Ltd. All rights reserved. Published^{/3}by WWW.SKYT 2010.01 - Rev.A



©2009 ROHM Co., Ltd. All rights reserved. Published/3by WWW.SKYTECH.Rey A



IRIOIEII

Thank you for your accessing to ROHM product informations. More detail product informations and catalogs are available, please contact us.

ROHM Customer Support System

http://www.rohm.com/contact/

R1010A