


## Glass Passivated Single-Phase Bridge Rectifier

### FEATURES

- Ideal for printed circuit board
- High case dielectric strength
- High surge current capability
- Typical IR less than 0.1uA
- UL Recognized File # E-326243
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



**KBP**



### MECHANICAL DATA

**Case:** Molded plastic body

Molding compound, UL flammability classification rating 94V-0


Base P/N with suffix "G" on packing code - halogen-free

**Terminal:** Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test

**Polarity:** Polarity as marked on the body

**Weight:** 1.54 g (approximately)



MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25°C unless otherwise noted)										
PARAMETER		SYMBOL	KBP 301G	KBP 302G	KBP 303G	KBP 304G	KBP 305G	KBP 306G	KBP 307G	UNIT
Maximum repetitive peak reverse voltage		V <sub>RRM</sub>	50	100	200	400	600	800	1000	V
Maximum RMS voltage		V <sub>RMS</sub>	35	70	140	280	420	560	700	V
Maximum DC blocking voltage		V <sub>DC</sub>	50	100	200	400	600	800	1000	V
Maximum average forward rectified current		I <sub>F(AV)</sub>	3							A
Peak forward surge current, 8.3 ms single half sine-wave	T <sub>J</sub> = 25°C	I <sub>FSM</sub>	80							A
	T <sub>J</sub> = 125°C		50							
Peak forward surge current, 1.0 ms single half sine-wave	T <sub>J</sub> = 25°C	I <sub>FSM</sub>	160							A
	T <sub>J</sub> = 125°C		100							
Rating of fusing ( t<8.3ms)		I <sup>2</sup> t	26.5							A <sup>2</sup> s
Maximum instantaneous forward voltage (Note 1) I <sub>F</sub> = 3 A		V <sub>F</sub>	1.1							V
Maximum reverse current @ rated VR    T <sub>J</sub> =25 °C T <sub>J</sub> =125 °C		I <sub>R</sub>	10							μA
			500							
Typical junction capacitance per leg (Note 2)		C <sub>j</sub>	215							pF
Typical thermal resistance		R <sub>θjL</sub>	11							°C/W
		R <sub>θjA</sub>	30							
Operating junction temperature range		T <sub>J</sub>	- 55 to +150							°C
Storage temperature range		T <sub>STG</sub>	- 55 to +150							°C

Note 1: Pulse test with PW=300μs, 1% duty cycle

Note 2: Measured at 1MHz and applied Reverse bias of 4.0V DC

ORDERING INFORMATION				
PART NO.	PACKING CODE	GREEN COMPOUND CODE	PACKAGE	PACKING
KBP30xG (Note 1)	C2	Suffix "G"	KBP	25 / Tube

Note 1: "x" defines voltage from 50V (KBP301G) to 1000V (KBP307G)

EXAMPLE				
PREFERRED P/N	PART NO.	PACKING CODE	GREEN COMPOUND CODE	DESCRIPTION
KBP306G C2	KBP306G	C2		
KBP306G C2G	KBP306G	C2	G	Green compound

## RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG.1 FORWARD CURRENT DERATING CURVE




FIG. 2 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT




FIG. 3 TYPICAL REVERSE CHARACTERISTICS




FIG. 4 TYPICAL FORWARD CHARACTERISTICS






FIG. 5 TYPICAL JUNCTION CAPACITANCE



PACKAGE OUTLINE DIMENSIONS



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	10.60	11.68	0.417	0.460
B	0.70	0.90	0.028	0.035
C	3.60	4.10	0.142	0.161
D	12.70	-	0.500	-
E	3.70	3.90	0.146	0.154
F	14.22	15.24	0.560	0.600
G	1.27	-	0.050	-

MARKING DIAGRAM



P/N = Specific Device Code  
G = Green Compound  
YW = Date Code  
F = Factory Code

Not Recommended

#### Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taiwan Semiconductor:

[KBP301G](#) [KBP302G](#) [KBP303G](#) [KBP304G](#) [KBP305G](#) [KBP306G](#) [KBP307G](#)